

AIO™ Ceiling Ducted – without ERV (Gen 3)

Product Data Sheet



CONTACT INFO

VIP Customer/Technical Support

Email: vip@innova.co

Phone: [\(212\) 204-2700](tel:(212)204-2700)

DISCLAIMER

This documentation is intended for informational use only and should not be construed as a binding representation or contract. This documentation is provided "as is" without warranty of any kind, either express or implied. INNOVA and its affiliates disclaim all liability arising from the use or misuse of this documentation.

Illustrations may not be to scale, and all information and dimensions stated herein are subject to change at any time at the sole discretion of INNOVA. Benefits described herein apply only to the extent that the product is installed correctly in the correct application and used for its intended purpose.

INNOVA is constantly innovating and improving its products and reserves the right to modify product design and specifications without notice and without incurring any obligations.

CERTIFICATIONS & LISTINGS

The AHRI Certified® mark indicates INNOVA's participation in the AHRI Certification program. For verification of individual certified products, go to www.ahridirectory.org.


ETL Listed. Control Number: 5032306. Conforms to: UL 60335-2-40:2022 Ed.4 | CSA C22.2#60335-2-40:2022 Ed.4 | UL 60335-1:2016 Ed.6 | CSA C22.2#60335-1:2016 Ed.2

MODEL NUMBER NOMENCLATURE

The code identifies the family, model, version, size, voltage, accessories, refrigerant type, and ERV option. See the diagram below for details.

Note: Mirror Version units use the suffix "-MR" in place of the generation code (e.g., "-3" or "-3SP"), indicating a mirrored (left/right reversed) unit configuration.

Figure 1. AIO™ Model Number Nomenclature



* 8" Vents : Just generation (e.g. = 3)

6" Vents : Generation + SP (e.g. = 3SP)

** Field convertible to 900W

*** AIO™ Vertical Stack XL Only

AIO® is a registered trademark of INNOVA.

Copyright © 2026 INNOVA. All rights reserved.

CONTENTS

1. READING THIS DOCUMENTATION.....	4
1.1 Documentation-specific language.....	4
1.2 Annotation icons.....	4
2. AIO™ CEILING DUCTED WITHOUT ERV OVERVIEW.....	4
2.1 Components and structure.....	4
2.2 Key features.....	5
3. AIRFLOW.....	5
3.1 Bottom Return (Special Field-Configured Option).....	6
3.2 Side Return (Standard Configuration).....	6
3.3 Fan curves.....	6
4. INSTALLATION.....	6
4.1 Air Balancing Requirements.....	7
4.2 Startup airflow commissioning.....	7
4.3 Low Ambient Heating Configuration Requirement.....	7
4.4 Ambient Temperature Protection.....	7
4.5 Site Requirements.....	7
4.6 Louver Specifications.....	8
4.7 Clearance Requirements.....	9
5. TECHNICAL SPECIFICATIONS.....	10
5.1 High Performance.....	10
5.1.1 Cooling.....	10
5.1.2 Heating - Heat pump only.....	10
5.2 Energy Star Compliant.....	10
5.2.1 Cooling.....	10
5.2.2 Heating - Heat pump only.....	11
5.3 Airflow.....	11
5.3.1 Indoor.....	11
5.3.2 Outdoor.....	11
5.4 Sound.....	11
5.5 General.....	11
5.5.1 Controls.....	11

5.5.2 Modes.....	11
5.5.3 Condensate.....	11
5.5.4 Compressor.....	12
5.5.5 Physical data.....	12
5.5.6 Insulation.....	12
5.6 Electrical.....	12
5.6.1 General.....	12
5.6.2 Compressor.....	12
5.6.3 Circuit breakers.....	12
5.6.4 Heater Output (W) and Heater Current (A) vs. Supply Voltage.....	13
6. WIRING DIAGRAM.....	13
6.1 Before January, 2026.....	13
6.2 After January, 2026.....	13
7. DIMENSIONS.....	14
7.1 Standard Configuration.....	14
8. WARRANTY.....	15
8.1 Basic Coverage.....	15
8.2 Optional Extended Coverage.....	15
8.3 Validation Requirements.....	15
9. SUBMITTALS.....	16
9.1 115V Heat pump only - High Performance.....	16
9.2 115V Heat pump + elec heat - High Performance.....	17
9.3 230V Heat pump only - High Performance.....	18
9.4 230V Heat pump + 1,800W elec heat - High Performance.....	19
9.5 230V Heat pump + 2,700W elec heat - High Performance.....	20
9.6 115V Heat pump only - Energy Star Compliant.....	21
9.7 115V Heat pump + elec heat - Energy Star Compliant.....	22
9.8 230V Heat pump only - Energy Star Compliant.....	23
9.9 230V Heat pump + 1,800W elec heat - Energy Star Compliant.....	24

9.10 230V Heat pump + 2,700W elec heat - Energy Star Compliant.....	25
---	----

1. READING THIS DOCUMENTATION

Some language and symbols in this documentation have specific meanings.

1.1 Documentation-specific language

Reference to the product

Any reference to “the unit” refers to the AIO™ Ceiling Ducted without ERV unit.

Unit orientation

All directions in this guide (left, right, top, bottom) are given from the perspective of facing the unit.

Mirrored unit orientation

Some units are available in a mirrored configuration, identified by the suffix “-MR” in the model number.

Mirror Version units are physically identical to standard units but with left and right orientations reversed.

Unless otherwise stated, all references to left and right in this document apply to the standard orientation.

1.2 Annotation icons

Annotations are provided throughout this guide. It is essential to read each carefully and follow the instructions stated.



Indicates critical information for correct operation or installation.



Indicates supplemental information, tips, or useful background information.

2. AIO™ CEILING DUCTED WITHOUT ERV OVERVIEW

An AIO™ Ceiling Ducted unit can be discreetly installed above a ceiling and is ideal for single-room or multi-room applications. The return can be from the sides or the bottom for maximum flexibility. With up to 0.6” (15.2 mm) external static pressure, this unit can be used where ducting is required. Use with any interior grille and louver to provide additional design flexibility.


Available in standard and mirrored configurations (suffix -MR), with identical performance and mirrored left/right layout.



Units are supplied with side returns as standard. If a bottom return is required, it must be specified at time of order and included on the approved estimate and purchase order.

2.1 Components and structure

Figure 2. What's inside



1	Condenser exhaust vent	10	High-efficiency indoor coil
2	Condenser exhaust fan	11	Controllers Connection Terminal
3	Twin rotary inverter compressor	12	ECM supply fan
4	Return air connection	13	Return air vent
5	Return air filter	14	Return air filter
6	ECM supply fan	15	Condenser intake
7	900/1800W electric heat strip	16	Condensate drain
8	Supply air connection	17	High efficiency outdoor coil
9	Onboard touch controller (underneath the unit)		



Component positions are mirrored in AIO™ Ceiling Ducted - Mirror Version units.

2.2 Key features

No outdoor unit

The single-package design means that there is no outdoor unit, freeing up space on rooftops and at ground level and enabling installations in buildings without space for an outdoor unit.

Twin rotary BLDC inverter compressor

The state-of-the-art, Twin Rotary Brushless DC (BLDC) inverter compressor operates efficiently, quietly, and with minimal vibration. The AIO™ Ceiling Ducted unit is ideal for any room or area that requires between 3,100 and 15,000 BTU/hr.

MERV 13 clean air

Clean outdoor air is essential to well-being and safety. The optional MERV 13 filter ensures that all air entering the room or home is clean and safe.

High-efficiency ECM fans with auto ESP

High-efficiency electronically commutated motor (ECM) fans enable efficient and quiet operation because the EC motor can ramp up or down as required. Automatically adjusted external static pressure ensures correct airflow.

Cold climate heat pump

The heat pump operates at full efficiency when outdoor temperatures are as low as 5°F (-15°C), and will still operate at colder temperatures below -5°F (-20.6°C).

Quiet

With whisper-quiet operation as low as 27 decibels, the occupant will barely notice that the AIO™ Ceiling Ducted unit is operating.

Intelligent defrosting

AIO™ Ceiling Ducted's intelligent defrosting system means more time heating and less time on reverse cycle defrost.

Optional 1,800/2,700-watt electric heat

The optional electric heating system operates alongside the heat pump when the heat pump lacks sufficient power. This electric heating setup consists of two/three 900W heaters, strategically staged to optimize efficiency while minimizing electric heat use. Depending on the unit ordered, it can offer multiple

configuration options for electric heat usage: it can be set to use no electric heat, or 900W/1,800W/2,700W of electric heat, providing flexibility and energy management capabilities.

Versatile on/off options

AIO™ Ceiling Ducted's low-voltage connection enables connection to any Building Management System (BMS), key-card system, window sensors, fire alarms, etc. As long as a system can send a signal to the AIO™ unit via low voltage, the unit can be easily turned on or off.

Minimal clearances and compact footprint

AIO™ Ceiling Ducted's compact form does not use any line sets. This means that there is no need to access the sides of the unit. You can mount units with as little as ¾" (19.1 mm) clearance on all sides. Compact footprints take up minimal space.

Leak protection

If a drain becomes clogged, the system shuts down, and an alarm is activated. This prevents water damage.

Easy to service

The AIO™ Ceiling Ducted unit can be easily maintained and repaired from underneath without having to remove the unit from the ceiling.

Versatile controls

The AIO™ Ceiling Ducted unit includes an onboard touch controller and an optional iOS and Android app. The unit can be used with optional wall-mounted controllers, including a Thin Film Transistor (TFT) with a 7-day program, and third-party controllers from any company, using the optional third-party kit. An optional BACnet and Modbus module enables interfacing with building management systems.

10-Year limited warranty

An industry-leading 10-year limited warranty provides peace of mind.

- Comprehensive onsite two-year parts and labor (after certification).
- 5-year parts warranty.
- 10-year parts warranty on the compressor.

See [Warranty Terms and Conditions](#) for details.

3. AIRFLOW



For Mirror Version units, all left and right airflow connections are reversed.

AIO™ Ceiling Ducted is flexible in many ways. It can be fully ducted or used with minimal or no ducting. This flexibility enables AIO™ Ceiling Ducted to be placed anywhere in the ceiling, without restrictions.

Supply air

The rectangular 3.9" x 30.3" (100 mm x 770 mm) supply air connection is ideal for a supply grille or ducting, with up to 0.6" WC (149.5 Pa) external static pressure (combined between return and supply).

Return air - bottom option


The bottom 8.7" x 32.3" (220 mm x 820 mm) return is designed to be used with a ceiling-mounted return grille or an access panel with an integrated return grille.

Return air-side options


The left and right side 6" (160 mm) round connections can be ducted to one or more rooms with up to 0.6" WC (149.5 Pa) external static pressure (combined between return and supply). It can also be left open as a side plenum return. With two ECM fans, each with auto ESP, each connection is fully independent. Duct both, leave both open, or duct one and leave one open to a plenum.

For optimal performance, a fully ducted return configuration is recommended. Both return air openings must remain open and unobstructed during operation. The unit may be installed with both returns ducted, or with one return ducted and the other left open as a side plenum return.

3.1 Bottom Return (Special Field-Configured Option)





3.2 Side Return (Standard Configuration)



3.3 Fan curves

The following graphs illustrate airflow versus external static pressure at low, medium, and high fan speeds.




4. INSTALLATION



Figure 9. Direct external vent



Figure 10. Shared supply and exhaust vent



4.1 Air Balancing Requirements

- All units must be properly air balanced by a qualified, professional air balancing company.
- Air balancing must be performed after installation and prior to final commissioning.
- A formal air balancing report must be completed and made available.
- Failure to perform air balancing properly may result in improper performance, system issues, and voiding of the warranty.

4.2 Startup airflow commissioning

Units require startup airflow commissioning. Select the indoor/outdoor airflow program to match the installed duct configuration and external static pressure. Adjust ERV ventilation airflow during startup and verify airflow in the field. See the [Installation Guide](#) for detailed setup and measurement procedures.

4.3 Low Ambient Heating Configuration Requirement

To configure the unit for electric resistance heating in low ambient conditions:

1. Turn on the unit.
2. Press and hold  for 10 seconds until "Fh" appears on the display.
3. Press and hold  for 5-10 seconds until "Fo" appears on the display.
4. Press and hold  for 5-10 seconds until "rE" appears on the display.
5. Wait a few seconds (without pressing any buttons) to exit the menu.

rE = Resistance heat mode

This setting switches the unit to electric resistance heating during low ambient conditions, preventing heat pump operation that may contribute to ice formation.

4.4 Ambient Temperature Protection

When installed in climates with ambient temperatures below freezing, the unit must be located in an enclosed, temperature-protected indoor space that will not fall below 5°F (-15°C).



Secure any installation site insulation so that it cannot detach or be drawn into the unit's air openings. Failure to secure insulation may lead to unit damage and will void the warranty.

4.5 Site Requirements



Refer to the installation manual for complete installation requirements and specifications.

- Where practical, avoid installing the unit in a location exposed to direct sunlight. Solar heating may cause the room-air temperature sensor to detect a temperature higher than the actual room temperature, resulting in improper temperature control, unnecessary cooling operation, reduced heating output, and decreased energy efficiency.
- Secure any installation site insulation so that it cannot detach or be drawn into the unit's air openings.
- A power supply circuit installed in accordance with the current edition of NEC (ANSI/NFPA 70) and local codes and ordinances.



- Always consult local and national electrical codes before installing the unit.
- Damage or premature failure of the quoted equipment resulting from improper voltage conditions, inadequate electrical service, or operating the equipment with excessive THD (Total Harmonic Distortion) levels will void the Manufacturer's warranty.



- Do not operate the unit in or near a construction or renovation site. Dust and debris can enter the unit, causing malfunctions and reduced performance.
- If the unit must be operated during construction or renovation, the air filters and accessible coil surfaces must be inspected and cleaned daily before operation.
- Failure to perform daily cleaning during construction use may result in damage and will void the warranty.

- A power supply with a voltage rating of 60 Hz, single phase, in 115V or 208/230V in accordance with the model specified.
- All responsible parties must verify that the electrical supply is properly grounded, free of excessive electrical noise, and within the specified voltage and frequency limits before energizing the unit. Failure to correct power quality issues, including voltage instability or electrical noise, may result in equipment damage and will void the warranty for affected components.
- Interior clearances are as follows:
 - Sides of unit to wall: 3.5" (88.9 mm)
 - Bottom of unit to floor: 11.8" (300 mm)
 - Top of unit to any obstruction: 1/8" (8.5 mm)

- Unblocked vents on the exterior and no obstacles within 36" (914.4 mm).
- An internal drain is highly recommended.
- If using an externally run condensate line, note the following:
 - The line must be properly insulated.
 - The line must have a minimum slope of 2%.
 - If on a low floor, ensure that the end of the drain is above the maximum height of snow buildup.
- Approved louvers must be installed with best practices to ensure that no water enters the wall assembly.
- The unit is intended for ducted installation. Installation without ductwork may result in airflow performance issues.
- 8" (203.2 mm) diameter ducts through the wall, which protrude 1/8" (3.2 mm) into the unit's EPDM backing to ensure a tight seal.
- The unit must be perfectly level on the horizontal axis and perfectly plumb on the vertical axis.
- The unit must be attached to the ducts tightly, with zero leakage between the external ducts and the unit.
- The wall bracket must be properly affixed to wall studs or other supporting material. Note that the wall bracket has several places that must be secured.

4.6 Louver Specifications

AIO™ Ceiling Ducted units can be vented through various custom and creative solutions. The possibilities are endless, from perforated panels to custom louvers.

There are three critical factors when selecting and sizing a solution that works with AIO™ Ceiling Ducted units.

- **Air-path separation:** When a field-supplied louver or louver assembly serves both the outdoor-air intake and exhaust, provide a continuous, airtight, insulated separator between the intake and exhaust air paths. The separator must extend through the plenum to the exterior

louver to prevent exhaust air from being drawn back into the intake. Exhaust-air recirculation can cause improper operation and unit short cycling.

- **Free area:** The area on a louver/grille that is open for the air to flow through. The louver, perforated panel, or other solution must have at least the amount of free area specified in the specifications below in the plenum from the unit, so that ample air can enter and exit the condenser chamber. A more restrictive solution with a smaller free area can be utilized by enlarging the louver and plenum until the required free area is achieved.



The minimum free area required is 0.34 square feet (0.03 square meters) for the intake vent and 0.34 square feet (0.03 square meters) for the exhaust vent.

- **Pressure drop:** Pressure drop is the resistance the louver/grille creates against the airflow. This resistance can create heat build-up inside the condenser portion, causing the compressor to overheat and shut down. A solution with a higher pressure drop than specified can be utilized by enlarging the louver and plenum until the pressure drop is within specification.



- The maximum total pressure for the intake and exhaust ducting (if any) and intake and exhaust louvers combined must be under 0.7 in. WC (174.4 Pa).
- Total air circuit system input and output pressure, including all ductwork, plenums, and louvers, may not exceed a maximum value of 0.7 in. WC (174.4 Pa)

- Any louver or louver assembly must meet these requirements, because exceeding these limits can cause the unit to overheat and fail. This will void the warranty.

- The following louvers are approved for AIO™ Ceiling Ducted units:
 - **Sunvent:** LLA/C, LLA/M, LLA/S – available through your INNOVA distributor.
 - **Therma duct:** RLA8 – available through your INNOVA distributor.

4.7 Clearance Requirements

The clearances for the AIO™ Ceiling Ducted unit depend on how it is vented. Carefully read the criteria below to determine the correct clearance required.



While these are the minimum clearances required for our units to operate, a greater clearance may be required by code. Always follow the stricter requirements.

• Ceiling

There must be a 2" (50 mm) minimum clearance between the unit and the ceiling to minimize noise from vibrations.

• Bottom


There must be a minimum of 2" (50 mm) clearance between the unit and the false ceiling or access panel to minimize noise from vibrations.

• Front (supply air side)

The clearance required in front of the unit to drywall or other material is 3.5" (90 mm) to minimize noise from vibration, and to ensure easy access for installation and maintenance.


• Rear (intake/exhaust side)

There must be a 3.5" (90 mm) minimum clearance between the unit and the wall to minimize noise from vibration, and to ensure easy access for installation and maintenance. Ensure sufficient clearance to attach ductwork to the rear vents.



• Access Panel

There must be an access panel of at least the size of the unit plus 3.5" (90 mm) all around. The minimum size is 45.0" × 49.3" (1142 mm × 1251 mm). A return grille can serve as an access panel, or an access panel with an integrated return grille can be used.



• Sides


The clearance required on the sides is dependent on how the unit is configured for return and stale exhaust air. Minimum clearance is required between the unit and the wall to minimize noise from vibrations. Ensure sufficient clearance to attach ductwork to the rear vents.

• Side ducted return configuration

The clearance required is based solely on the

ductwork design. Ensure sufficient clearance to attach the ductwork to the side return.


Figure 13. Side ducted return configuration



• Side non-ducted return configuration

A minimum of 3.5" (90 mm) should be free on each side to allow the air to flow into the returns, and to ensure easy access for installation and maintenance.

Figure 14. Side plenum return configuration



Exterior

On the exterior of the building, there should be no obstacles blocking the airflow from the louver. There must be at least 36" (915 mm) of free and clear space in front of the louvers.

5. TECHNICAL SPECIFICATIONS

5.1 High Performance

5.1.1 Cooling

Table 1. High Performance - Cooling

Heat Pump			95°F (35°C) (1)	105°F (40.6°C) (2)	115°F (46.1°C) (3)
Capacity	Maximum	BTU/hr	15,000	11,400	9,825
	Recommended*		9,400	8,200	7,300
	Rated		7,700	7,345	6,550
	Minimum		3,100	3,100	3,100
Input Power	Maximum	W	1,580	1,640	1,700
	Recommended*		960	950	1,040
	Rated		732	825	904
	Minimum		230	255	285
Efficiency	Maximum	EER	9.49	6.96	5.78
	Recommended*		9.79	8.63	7.02
	Rated		EER2 10.55	8.90	7.25
	Seasonal		SEER2 13.85	-	-
Moisture Removal		Pts/h	1.8	2.0	2.2
		L/hr	0.9	0.9	1.0

Notes

- (1) ID: 80°F(26.7°C), W.B. 67°F(19.4°C) | OD: 95°F(35°C), W.B. 75°F(23.9°C)
 (2) ID: 80°F(26.7°C), W.B. 67°F(19.4°C) | OD: 105°F(40.6°C), W.B. 75°F(23.9°C)
 (3) ID: 80°F(26.7°C), W.B. 67°F(19.4°C) | OD: 115°F(46.1°C), W.B. 75°F(23.9°C)

* This is the recommended capacity for sizing the unit to the space.

5.1.2 Heating - Heat pump only

Table 2. High Performance - Heating

Heat Pump			47°F (8.3°C) (1)	17°F (-8.3°C) (2)	5°F (-15°C) (3)	0°F (-17.8°C) (4)	-5°F (-20.6°C) (5)
Capacity	Maximum	BTU/hr	14,000	10,000	6,600	6,300	5,800
	Recommended*		9,200	8,300	6,200	5,935	5,570
	Rated		8,600	8,300	6,200	5,935	5,570
	Minimum		3,500	3,300	2,800	2,500	2,500
Input Power	Maximum	W	1,420	1,460	1,700	1,600	1,650
	Recommended*		774	860	1,250	1,062	1,013
	Rated		693	860	1,086	1,062	1,013
	Minimum		315	420	440	430	480
Efficiency	Maximum	COP	2.89	2.01	1.13	1.14	1.04
	Recommended*		3.48	2.83	1.45	1.64	1.61
	Rated		3.64	2.83	1.68	1.64	1.61
	Minimum		3.26	2.30	1.87	1.70	1.53
	Seasonal	HSPF 2	9.15	-	-	-	-

Notes

- (1) ID: 70°F(21.1°C), W.B. 60°F(15.6°C) | OD: 47°F(8.3°C), W.B. 43°F(6.1°C)
 (2) ID: 70°F(21.1°C), W.B. 60°F(15.6°C) | OD: 17°F(-8.3°C), W.B. 13°F(-10.6°C)
 (3) ID: 70°F(21.1°C), W.B. 60°F(15.6°C) | OD: 5°F(-15°C), W.B. 3°F(-16.1°C)
 (4) ID: 70°F(21.1°C), W.B. 60°F(15.6°C) | OD: 0°F(-17.8°C)
 (5) ID: 70°F(21.1°C), W.B. 60°F(15.6°C) | OD: -5°F(-20.6°C)

* This is the recommended capacity for sizing the unit to the space.



Optional heat strips are available for an additional 6,100 BTU/hr of heating capacity.

5.2 Energy Star Compliant

5.2.1 Cooling

Table 3. Energy Star Compliant - Cooling

Heat Pump			95°F (35°C) (1)	105°F (40.6°C) (2)	115°F (46.1°C) (3)
Capacity	Maximum	BTU/hr	15,000	11,400	9,825
	Recommended*		9,400	8,200	7,300
	Rated		6,100	7,345	6,550
	Minimum		3,100	3,100	3,100
Input Power	Maximum	W	1,580	1,640	1,700
	Recommended*		960	950	1,040
	Rated		528	825	904
	Minimum		230	255	285
Efficiency	Maximum	EER	9.49	6.96	5.78
	Recommended*		9.79	8.63	7.00
	Rated	EER2	11.56	8.90	7.25
	Seasonal	SEER2	15.3	-	-
Moisture Removal		Pts/h	1.8	2.0	2.2
		L/hr	0.9	0.9	1.0

Notes

- (1) ID: 80°F(26.7°C), W.B. 67°F(19.4°C) | OD: 95°F(35°C), W.B. 75°F(23.9°C)
 (2) ID: 80°F(26.7°C), W.B. 67°F(19.4°C) | OD: 105°F(40.6°C), W.B. 75°F(23.9°C)
 (3) ID: 80°F(26.7°C), W.B. 67°F(19.4°C) | OD: 115°F(46.1°C), W.B. 75°F(23.9°C)

* This is the recommended capacity for sizing the unit to the space.

5.2.2 Heating – Heat pump only

Table 4. Energy Star Compliant – Heating

Heat Pump			47°F (8.3°C) (1)	17°F (-8.3°C) (2)	5°F (-15°C) (3)	0°F (-17.8°C) (4)	-5°F (-20.6°C) (5)
Capacity	Maximum	BTU/hr	14,000	10,000	6,600	6,300	5,800
	Recommended*		9,200	7,800	5,900	5,935	5,570
	Rated		8,200	7,800	5,900	5,935	5,570
	Minimum		3,500	3,300	2,800	2,500	3,300
Input Power	Maximum	W	1,420	1,460	1,700	1,600	1,650
	Recommended*		674	760	1,140	1,062	1,013
	Rated		693	760	988	1,062	1,013
	Minimum		315	420	440	430	480
Efficiency	Maximum	COP	2.89	2.01	1.13	1.14	1.04
	Recommended*		3.48	3.01	1.52	1.64	1.61
	Rated		3.73	3.01	1.75	1.64	1.61
	Minimum		3.26	2.30	1.87	1.70	2.01
	Seasonal	HSPF 2	9.2	-	-	-	-

Notes

- (6) ID: 70°F(21.1°C), W.B. 60°F(15.6°C) | OD: 47°F(8.3°C), W.B. 43°F(6.1°C)
 (7) ID: 70°F(21.1°C), W.B. 60°F(15.6°C) | OD: 17°F(-8.3°C), W.B. 13°F(-10.6°C)
 (8) ID: 70°F(21.1°C), W.B. 60°F(15.6°C) | OD: 5°F(-15°C), W.B. 3°F(-16.1°C)
 (9) ID: 70°F(21.1°C), W.B. 60°F(15.6°C) | OD: 0°F(-17.8°C)
 (10) ID: 70°F(21.1°C), W.B. 60°F(15.6°C) | OD: -5°F(-20.6°C)

* This is the recommended capacity for sizing the unit to the space.



Optional heat strips are available for an additional 6,100 BTU/hr of heating capacity.


5.3 Airflow

5.3.1 Indoor

Table 5. Airflow – Indoor

Air volume		
Indoor	Type	ECM centrifugal
	CFM Range	226 – 400
	m ³ /hr	384– 680
	Available ESP	0.6" WC (149.5 Pa)
	Supply connection	3.9" (100 mm) H x 27.9" (708 mm) W
	Return connection	Two 6" (152 mm) round on sides or bottom 8.7" x 32.3" (220 mm x 820 mm)
	Speeds	Low, med, high, boost, auto
	Filter	MERV 3

Figure 15. MERV Filter Pressure Drop



5.3.2 Outdoor

Table 6. Airflow – Outdoor

Air volume		
Outdoor	Type	ECM centrifugal
	CFM Range	385 – 638
	m ³ /hr Range	654– 1084
	Nominal CFM	400
	Nominal m ³ /hr	680
	Available ESP at Nominal	0.7" WC (174.4 Pa)
	Intake and Exhaust Connection	8" (203 mm) round
	Speeds	Low, med, high, auto

5.4 Sound

Table 7. Sound

Sound			
Location	Distance	Fan Speed	Sound Level (dB(A))
Indoor	1 m	Level 1 – Low	38
		Level 2 – Medium	48
		Level 3 – High	49
	3 m	Level 1 – Low	30
		Level 2 – Medium	40
		Level 3 – High	41
Outdoor	-	Range	28 – 55

5.5 General

5.5.1 Controls

Table 8. Controls

Controls	
Basic functionality	Dependent on the controller
WiFi	Optional module available
Dry contact	Yes
Power outage restart	Auto-on based on the last setting

5.5.2 Modes

Table 9. Modes

Modes	
Operation	Cool+ fresh air, cool only, heat+ fresh air, heat only, auto
Restricted modes	Heat only, cool only, temperature limiting
Timers	Dependent on the controller

5.5.3 Condensate

Table 10. Condensate

Condensate	
Pipe size	3/4" (19 mm) outside diameter
Pipe material	Rubber

5.5.4 Compressor

Table 11. Compressor

Compressor			
Type	BLDC twin rotary inverter		
Refrigerant	For R-32 Units	Refrigerant Type	R-32
		Charge	16.93 oz. 480 g
	For R-410A Units	Refrigerant Type	R-410A
		Charge	23.97 oz. 680 g
Oil Type	Fv50s (ISO 50) Polyvinylether (PVE)		

5.5.5 Physical data



For detailed dimensions, refer to the drawings in [Section 7](#).

Table 12. Physical data

Physical data			
Dimensions	Cabinet Only	in	39.5 W x 40.1 D x 11 H
		mm	1003 W x 1018 D x 279 H
	Overall Installed (Minimum)	in	41.4 W x 42.7 D x 11 H
		mm	1052 W x 1085 D x 279 H
Weight	Net	lb	178
		kg	80.7
	Gross	lb	190
		kg	86.1
Cabinet	Finish	Black covered with dark gray EPDM	
	Material	Steel	

5.5.6 Insulation


Table 13. General - Insulation

Thermal conductivity at 50°F	0.239 BTU*in/(hr-ft²*°F)
Thermal conductivity at 10°C	0.0344 W/(m·K)



Insulation R-value is determined by dividing the insulation thickness by the thermal conductivity (k-value). Insulation thickness varies by component and configuration.

Figure 16. Insulation Thickness



5.6 Electrical

5.6.1 General

Table 14. General

General		115V	230V
Volt range		103 - 127	180-253
Hz/phase		60 Hz / single phase	
Power input connection		Hardwire	
Power factor		0.96	
Input power (standby)	W	10.8	
Input power (off mode)		1.5	
Heat Pump Only			
Cooling (nominal)	A	8.2	4.1
Cooling - heat pump (max)		19.1	8.6
Heating - heat pump (nominal)	A	10.0	5.0
Heating-heat pump + (max)		19.1	8.6
Heat Pump + 900 W Elec Heater			
Maximum	A	27.3	-
Heat Pump + 1,800 W Elec Heater			
Maximum	A	-	16.4
Heat Pump + 2,700 W Elec Heater			
Maximum	A	-	20.3

5.6.2 Compressor

Table 15. General

Compressor			115V	208V	230V	240V
Compressor	RLA	A	13.0	6.6	6	5.8
	LRA		13.0	6.6	6	5.8
Indoor ECM fan motor	Watts (max)	W	260	200		
	FLA	A	3.4	1.33	1.2	1.15
	Power	HP	0.125	0.10		
Outdoor ECM fan motor	Watts (max)	W	150	150		
	FLA	A	2.1	1.16	1.05	1.01
	Power	HP	0.10	0.10		

5.6.3 Circuit breakers

Table 16. Circuit breakers

Circuit breakers			115V	208V	230V	240V
Heat Pump	MCA	A	23	12	11	10
	MOCP		35	15	15	15

Circuit breakers		115V	208V	230V	240V
Heat Pump + 900W Elec Heat	MCA	31	–	–	–
	MOCP	40	–	–	–
Heat Pump + 1800W Elec Heat	MCA	–	19	18	18
	MOCP	–	20	20	20
Heat Pump + 2700W Elec Heat	MCA	–	22	22	23
	MOCP	–	25	25	25

5.6.4 Heater Output (W) and Heater Current (A) vs. Supply Voltage

Table 17. Heater Output (W) and Heater Current (A) vs. Supply Voltage


Volt/Watt	1000W	900W	1800W	2700W
115V	N/A	900W / 7.8A	N/A	N/A
208V	818W / 3.9A	736W / 3.5A	1472W / 7.1A	2200W / 10.6A
230V	1000W / 4.3A	900W / 3.9A	1800W / 7.8A	2700W / 11.7A
240V	1089W / 4.5A	980W / 4.1A	1960W / 8.2A	3000W / 12.5A

6. WIRING DIAGRAM

6.1 Before January, 2026

To view the diagram as a high-resolution PDF, click the link below:


[PDF AIO Ceiling Ducted Wiring Diagram \(Pre-Jan 2026\)](#)



6.2 After January, 2026

To view the diagram as a high-resolution PDF, click the link below:

[PDF AIO Ceiling Ducted Wiring Diagram \(Post-Jan 2026\)](#)



7. DIMENSIONS

7.1 Standard Configuration

To view the dimensions as a high-resolution PDF, click the link below:

[AIO - DIMS Ceiling Ducted.pdf](#)

Figure 19. Unit Dimensions




Figure 20. Unit Dimensions (Top View)




Figure 21. Unit Dimensions (Left View)




Figure 22. Unit Dimensions (Front View)




Figure 23. Unit Dimensions (Right View)




Figure 24. Unit Dimensions (Bottom View)





Figure 25. Unit Dimensions (Rear View)



8. WARRANTY

8.1 Basic Coverage

- **Parts:** 5 years from delivery.
- **Compressor:** 10 years from delivery.
- **Labor:** 2 years from certification (only if at least 10 units are installed, the site is certified by INNOVA or self-certified, and spare stock equal to 3% of total units is maintained)
- **Controllers:** Covered under a 2-year warranty.

8.2 Optional Extended Coverage

- **Additional 2-Year Parts & Labor Warranty:**
Extends the basic coverage to 4 years labor and 7 years parts.
- **Extended 10-Year Parts Warranty:** Extends parts coverage to 10 years total.
- **Extended 5-Year Full Warranty:** Extends full parts and labor coverage to 5 years total.
- **Extended 10-Year Full Warranty:** Provides a 10-year full warranty on parts, labor, and compressor.
- **Extended 15-Year Full Warranty:** Provides a 15-year full warranty on parts, labor, and compressor.

8.3 Validation Requirements

- Installation must be certified by an INNOVA technician or self-certified within 30 days.
- Installers must complete INNOVA training.
- The system must comply with local codes, use approved louvers, and be properly maintained (e.g., clean filters monthly, coils every 18 months).

For warranty service or claims, contact INNOVA Support at VIP@innova.co or [\(212\) 204-2700](tel:212-204-2700).

For detailed terms and conditions, click the link below:

 [AIO Warranty Terms and Conditions - 2026 - INN...](#)

9. SUBMITTALS

9.1 115V Heat pump only - High Performance

AIO™ CEILING DUCTED 115V - NO ELECTRIC HEAT STRIP
-R32 - SUBMITTAL (ADP10N3HI)


Job	Reference	Construction
Location	Approval	Quote Number
Engineer	Date	Drawing Number
Submitted To	Submitted By	P.O. Number

General Features

- BLDC inverter compressor
- Onboard touch controller
- ECM fans
- Washable filter
- R32 Refrigerant
- 4 selectable fan speeds + Auto
- Auto restart
- 10-Year limited warranty (after certification)
- Intelligent defrost
- Made in Italy
- No outdoor unit



The installing contractor must contact INNOVA Customer Technical Support prior to installation to schedule an installation training overview. This may be conducted in person or remotely (online). It is the official installation training and may include videos, best practices, and system requirements. Performing installations without training may result in installation errors, performance issues, and possible warranty limitations.



Performance Specifications			
Cooling	Min-Max	BTU/H	15,000 - 3,100
	Rated capacity (95°F)		7,700
	Efficiency	EER2	10.55
Heating	Min-Max	BTU/H	14,000 - 3,500
	Rated capacity (47°F)		8,600
	Rated capacity (5°F)		6,200
Sound	Indoor: Low-High at 1 m distance	db(A)	38 - 49
	Indoor: Low-High at 3 m distance		30 - 41
	Outdoor sound range		28 - 55
Moisture removal	Moisture removal	Pts/h	1.8
		L/hr	0.9
Airflow	Indoor	CFM	226 - 400
		m³/hr	384 - 680
	Outdoor	CFM	385 - 638
		m³/hr	654 - 1084

Electric Specifications	
Power Supply	115V/1Ph/60Hz
Voltage Range	103-127
Running Amps Cooling	8.2
Running Amps Heating	10.0
MCA	23
Maximum Overcurrent Protection (A)	35
Max Power Input (amps) Cooling	19.1
Max Power Input (amps) Heating	19.1

Included	Wall Controllers + Gateways	
☐	Wireless Remote	WRCH20
☐	Recessed Touch Controller	RTCH20
☐	Advanced TFT Controller with 7-Day program	TFTH20
☐	Third Party Gateway	TPG015
☐	WiFi Module	WIFI30
☐	E-Paper EOS Controller	EEOS12
☐	Simple EOS Controller	SEOS12
☐	Integration gateway for LTCH20, TFTH20 and MODBUS	GWN
☐	Integration gateway for LTCH20, TFTH20, MODBUS, BACnet, and third-party thermostats	GWX



Bottom return configuration (if required) must be specified at time of order. Standard units are supplied with side returns.

9.2 115V Heat pump + elec heat – High Performance

AIO™ CEILING DUCTED 115V + 900W ELECTRIC HEAT – R32 – SUBMITTAL (ADE10N3HI)


Job	Reference	Construction
Location	Approval	Quote Number
Engineer	Date	Drawing Number
Submitted To	Submitted By	P.O. Number

General Features

- BLDC inverter compressor
- ECM fans
- 900W Electric heat supplement
- R32 Refrigerant
- Auto restart
- Intelligent defrost
- No outdoor unit
- Onboard touch controller
- Washable filter
- 4 selectable fan speeds + Auto
- 10-Year limited warranty (after certification)
- Made in Italy



The installing contractor must contact INNOVA Customer Technical Support prior to installation to schedule an installation training overview. This may be conducted in person or remotely (online). It is the official installation training and may include videos, best practices, and system requirements. Performing installations without training may result in installation errors, performance issues, and possible warranty limitations.



Performance Specifications			
Cooling	Min-Max	BTU/H	15,000 – 3,100
	Rated capacity (95°F)		7,700
	Efficiency	EER2	10.55
Heating	Min-Max	BTU/H	14,000 – 3,500
	Rated capacity (47°F)		8,600
	Rated capacity (5°F)		6,200
	Efficiency	COP	3.64
Sound	Indoor: Low-High at 1 m distance	db(A)	38 – 49
	Indoor: Low-High at 3 m distance		30 – 41
	Outdoor sound range		28 – 55
Moisture removal	Moisture removal	Pts/h	1.8
		L/hr	0.9
Airflow	Indoor	CFM	226 – 400
		m³/hr	384 – 680
	Outdoor	CFM	385 – 638
		m³/hr	654 – 1084

Electric Specifications	
Power Supply	115V/1Ph/60Hz
Voltage Range	103-127
Running Amps Cooling	8.2
Running Amps Heating	10.0
MCA	31
Maximum Overcurrent Protection (A)	40
Max Power Input (amps) Cooling	19.1
Max Power Input (amps) Heating	27.3

Included	Wall Controllers + Gateways	
☐	Wireless Remote	WRCH20
☐	Recessed Touch Controller	RTCH20
☐	Advanced TFT Controller with 7-Day program	TFTH20
☐	Third Party Gateway	TPG015
☐	WiFi Module	WIFI30
☐	E-Paper EOS Controller	EEOS12
☐	Simple EOS Controller	SEOS12
☐	Integration gateway for LTCH20, TFTH20 and MODBUS	GWN
☐	Integration gateway for LTCH20, TFTH20, MODBUS, BACnet, and third-party thermostats	GWX



Bottom return configuration (if required) must be specified at time of order. Standard units are supplied with side returns.

9.3 230V Heat pump only - High Performance

AIO™ CEILING DUCTED 230V - NO ELECTRIC HEAT STRIP
-R32 - SUBMITTAL (ADP10N3H2)


Job	Reference	Construction
Location	Approval	Quote Number
Engineer	Date	Drawing Number
Submitted To	Submitted By	P.O. Number

General Features

- BLDC inverter compressor
- ECM fans
- R32 Refrigerant
- Auto restart
- Intelligent defrost
- No outdoor unit
- Onboard touch controller
- Washable filter
- 4 selectable fan speeds + Auto
- 10-Year limited warranty (after certification)
- Made in Italy



The installing contractor must contact INNOVA Customer Technical Support prior to installation to schedule an installation training overview. This may be conducted in person or remotely (online). It is the official installation training and may include videos, best practices, and system requirements. Performing installations without training may result in installation errors, performance issues, and possible warranty limitations.



Performance Specifications			
Cooling	Min-Max	BTU/H	15,000 - 3,100
	Rated capacity (95°F)		7,700
	Efficiency	EER2	10.55
Heating	Min-Max	BTU/H	14,000 - 3,500
	Rated capacity (47°F)		8,600
	Rated capacity (5°F)		6,200
	Efficiency	COP	3.64
Sound	Indoor: Low-High at 1 m distance	db(A)	38 - 49
	Indoor: Low-High at 3 m distance		30 - 41
	Outdoor sound range		28 - 55
Moisture removal	Moisture removal	Pts/h	1.8
		L/hr	0.9
Airflow	Indoor	CFM	226 - 400
		m³/hr	384 - 680
	Outdoor	CFM	385 - 638
		m³/hr	654 - 1084

Electric Specifications	
Power Supply	230V/1Ph/60Hz
Voltage Range	180-253
Running Amps Cooling	4.1
Running Amps Heating	5.0
MCA	11
Maximum Overcurrent Protection (A)	15
Max Power Input (amps) Cooling	8.6
Max Power Input (amps) Heating	8.6

Included	Wall Controllers + Gateways	
☐	Wireless Remote	WRCH20
☐	Basic Touch Controller	LTCH20
☐	Recessed Touch Controller	RTCH20
☐	Advanced TFT Controller with 7-Day program	TFTH20
☐	Wireless (AA Battery) Infrared Controller with 7-Day program	WIPT20
☐	Third Party Gateway	TPG015
☐	WiFi Module	WIFI30
☐	E-Paper EOS Controller	EEOS12
☐	Simple EOS Controller	SEOS12
☐	Integration gateway for LTCH20, TFTH20 and MODBUS	GWN
☐	Integration gateway for LTCH20, TFTH20, MODBUS, BACnet, and third-party thermostats	GWX



Bottom return configuration (if required) must be specified at time of order. Standard units are supplied with side returns.

9.4 230V Heat pump + 1,800W elec heat – High Performance

AIO™ CEILING DUCTED 230V + 1800W ELECTRIC HEAT – R32 – SUBMITTAL (ADK10N3H2)


Job	Reference	Construction
Location	Approval	Quote Number
Engineer	Date	Drawing Number
Submitted To	Submitted By	P.O. Number

General Features

- BLDC inverter compressor
- ECM fans
- 900/1800W Electric heat supplement
- R32 Refrigerant
- Auto restart
- Intelligent defrost
- No outdoor unit
- Onboard touch controller
- Washable filter
- 4 selectable fan speeds + Auto
- 10-Year limited warranty (after certification)
- Made in Italy



The installing contractor must contact INNOVA Customer Technical Support prior to installation to schedule an installation training overview. This may be conducted in person or remotely (online). It is the official installation training and may include videos, best practices, and system requirements. Performing installations without training may result in installation errors, performance issues, and possible warranty limitations.



Performance Specifications			
Cooling	Min-Max	BTU/H	15,000 – 3,100
	Rated capacity (95°F)		7,700
	Efficiency	EER2	10.55
Heating	Min-Max	BTU/H	14,000 – 3,500
	Rated capacity (47°F)		8,600
	Rated capacity (5°F)		6,200
	Efficiency	COP	3.64
Sound	Indoor: Low-High at 1 m distance	db(A)	38 – 49
	Indoor: Low-High at 3 m distance		30 – 41
	Outdoor sound range		28 – 55
Moisture removal	Moisture removal	Pts/h	1.8
		L/hr	0.9
Airflow	Indoor	CFM	226 – 400
		m³/hr	384 – 680
	Outdoor	CFM	385 – 638
		m³/hr	654 – 1084

Electric Specifications	
Power Supply	230V/1Ph/60Hz
Voltage Range	180-253
Running Amps Cooling	4.1
Running Amps Heating	5.0
MCA	18
Maximum Overcurrent Protection (A)	20
Max Power Input (amps) Cooling	8.6
Max Power Input (amps) Heating	16.4

Included	Wall Controllers + Gateways	
☐	Wireless Remote	WRCH20
☐	Recessed Touch Controller	RTCH20
☐	Advanced TFT Controller with 7-Day program	TFTH20
☐	Third Party Gateway	TPG015
☐	WiFi Module	WIFI30
☐	E-Paper EOS Controller	EEOS12
☐	Simple EOS Controller	SEOS12
☐	Integration gateway for LTCH20, TFTH20 and MODBUS	GWN
☐	Integration gateway for LTCH20, TFTH20, MODBUS, BACnet, and third-party thermostats	GWX



Bottom return configuration (if required) must be specified at time of order. Standard units are supplied with side returns.

9.5 230V Heat pump + 2,700W elec heat – High Performance

AIO™ CEILING DUCTED – 230V + 2,700W ELEC. HEAT – R32
– SUBMITTAL (ADL10N3H2)

Job	Reference	Construction
Location	Approval	Quote Number
Engineer	Date	Drawing Number
Submitted To	Submitted By:	P.O. Number:

General Features


- BLDC inverter compressor
- ECM fans
- Field configured 900W, 1,800W or 2,700W electric heat supplement
- Bathroom exhaust connection
- R32 Refrigerant
- Auto restart
- Intelligent defrost
- No outdoor unit
- Onboard touch controller
- Washable filter
- 4 selectable fan speeds + Auto
- 10-Year limited warranty (after certification)
- Made in Italy



The installing contractor must contact INNOVA Customer Technical Support prior to installation to schedule an installation training overview.

This may be conducted in person or remotely (online) It is the official installation training and may include videos, best practices, and system requirements.

Performing installations without training may result in installation errors, performance issues, and possible warranty limitations.



Performance Specifications			
Cooling	Min-Max	BTU/H	3,100 – 15,000
	Rated capacity (95°F)		7,700
	Efficiency	EER2	10.55
Heating	Min-Max	BTU/H	3,500 – 14,000
	Rated capacity (47°F)		8,600
	Rated capacity (5°F)		6,200
	Efficiency	COP	3.64
Sound	Indoor: Low-High at 1 m distance	db(A)	38 – 49
	Indoor: Low-High at 3 m distance		30 – 41
	Outdoor sound range		28 – 55
Moisture removal	Moisture removal	Pts/h	1.8
		L/hr	0.9
Airflow	Indoor	CFM	226 – 400
		m³/hr	384 – 680
	Outdoor	CFM	385 – 638
		m³/hr	654 – 1084

Electric Specifications	
Power Supply	230V/1Ph/60Hz
Voltage Range	180–253
Running Amps Cooling	4.1
Running Amps Heating	5.0
MCA	22
Maximum Overcurrent Protection (A)	25
Max Power Input (amps) Cooling	8.6
Max Power Input (amps) Heating	20.3

Included	Wall Controllers + Gateways	
☐	Wireless Remote	WRCH20
☐	Basic Touch Controller	LTCH20
☐	Recessed Touch Controller	RTCH20
☐	Advanced TFT Controller with 7-Day program	TFTH20
☐	Wireless (AA Battery) Infrared Controller with 7-Day program	WIPT20
☐	Third Party Gateway	TPG015
☐	WiFi Module	WIFI30
☐	E-Paper EOS Controller	EEOS12
☐	Simple EOS Controller	SEOS12
☐	Integration gateway for LTCH20, TFTH20 and MODBUS	GWN
☐	Integration gateway for LTCH20, TFTH20, MODBUS, BACnet, and third-party thermostats	GWX



Bottom return configuration (if required) must be specified at time of order. Standard units are supplied with side returns.

9.6 115V Heat pump only – Energy Star Compliant

AIO™ CEILING DUCTED 115V – NO ELECTRIC HEAT STRIP
-R32 – SUBMITTAL (ADP09N3H1)

Job	Reference	Construction
Location	Approval	Quote Number
Engineer	Date	Drawing Number
Submitted To	Submitted By	P.O. Number

General Features


- BLDC inverter compressor
- Onboard touch controller
- ECM fans
- Washable filter
- R32 Refrigerant
- 4 selectable fan speeds + Auto
- Auto restart
- 10-Year limited warranty (after certification)
- Intelligent defrost
- Made in Italy
- No outdoor unit



The installing contractor must contact INNOVA Customer Technical Support prior to installation to schedule an installation training overview.

This may be conducted in person or remotely (online). It is the official installation training and may include videos, best practices, and system requirements.

Performing installations without training may result in installation errors, performance issues, and possible warranty limitations.



Performance Specifications			
Cooling	Min-Max	BTU/H	15,000 – 3,100
	Rated capacity (95°F)		6,100
	Efficiency	EER2	11.56
Heating	Min-Max	BTU/H	14,000 – 3,500
	Rated capacity (47°F)		8,200
	Rated capacity (5°F)		5,900
	Efficiency	COP	3.73
Sound	Indoor: Low-High at 1 m distance	db(A)	38 – 49
	Indoor: Low-High at 3 m distance		30 – 41
	Outdoor sound range		28 – 55
Moisture removal	Moisture removal	Pts/h	1.8
		L/hr	0.9
Airflow	Indoor	CFM	226 – 400
		m³/hr	384 – 680
	Outdoor	CFM	385 – 638
		m³/hr	654 – 1084

Electric Specifications	
Power Supply	115V/1Ph/60Hz
Voltage Range	103-127
Running Amps Cooling	8.2
Running Amps Heating	10.0
MCA	23
Maximum Overcurrent Protection (A)	35
Max Power Input (amps) Cooling	19.1
Max Power Input (amps) Heating	19.1

Included	Wall Controllers + Gateways	
☐	Wireless Remote	WRCH20
☐	Recessed Touch Controller	RTCH20
☐	Advanced TFT Controller with 7-Day program	TFTH20
☐	Third Party Gateway	TPG015
☐	WiFi Module	WIFI30
☐	E-Paper EOS Controller	EEOS12
☐	Simple EOS Controller	SEOS12
☐	Integration gateway for LTCH20, TFTH20 and MODBUS	GWN
☐	Integration gateway for LTCH20, TFTH20, MODBUS, BACnet, and third-party thermostats	GWX



Bottom return configuration (if required) must be specified at time of order. Standard units are supplied with side returns.

9.7 115V Heat pump + elec heat - Energy Star Compliant

AIO™ CEILING DUCTED 115V + 900W ELECTRIC HEAT -
R32 - SUBMITTAL (ADE09N3H1)


Job	Reference	Construction
Location	Approval	Quote Number
Engineer	Date	Drawing Number
Submitted To	Submitted By	P.O. Number

General Features

- BLDC inverter compressor
- ECM fans
- 900 Electric heat supplement
- R32 Refrigerant
- Auto restart
- Intelligent defrost
- No outdoor unit
- Onboard touch controller
- Washable filter
- 4 selectable fan speeds + Auto
- 10-Year limited warranty (after certification)
- Made in Italy



The installing contractor must contact INNOVA Customer Technical Support prior to installation to schedule an installation training overview. This may be conducted in person or remotely (online). It is the official installation training and may include videos, best practices, and system requirements. Performing installations without training may result in installation errors, performance issues, and possible warranty limitations.



Performance Specifications			
Cooling	Min-Max	BTU/H	15,000 - 3,100
	Rated capacity (95°F)		6,100
	Efficiency	EER2	11.56
Heating	Min-Max	BTU/H	14,000 - 3,500
	Rated capacity (47°F)		8,200
	Rated capacity (5°F)		5,900
	Efficiency	COP	3.73
Sound	Indoor: Low-High at 1 m distance	db(A)	38 - 49
	Indoor: Low-High at 3 m distance		30 - 41
	Outdoor sound range		28 - 55
Moisture removal	Moisture removal	Pts/h	1.8
		L/hr	0.9
Airflow	Indoor	CFM	226 - 400
		m³/hr	384 - 680
	Outdoor	CFM	385 - 638
		m³/hr	654 - 1084

Electric Specifications	
Power Supply	115V/1Ph/60Hz
Voltage Range	103-127
Running Amps Cooling	8.2
Running Amps Heating	10.0
MCA	31
Maximum Overcurrent Protection (A)	40
Max Power Input (amps) Cooling	19.1
Max Power Input (amps) Heating	27.3

Included	Wall Controllers + Gateways	
☐	Wireless Remote	WRCH20
☐	Recessed Touch Controller	RTCH20
☐	Advanced TFT Controller with 7-Day program	TFTH20
☐	Third Party Gateway	TPG015
☐	WiFi Module	WIFI30
☐	E-Paper EOS Controller	EEOS12
☐	Simple EOS Controller	SEOS12
☐	Integration gateway for LTCH20, TFTH20 and MODBUS	GWN
☐	Integration gateway for LTCH20, TFTH20, MODBUS, BACnet, and third-party thermostats	GWX



Bottom return configuration (if required) must be specified at time of order. Standard units are supplied with side returns.

9.8 230V Heat pump only – Energy Star Compliant

AIO™ CEILING DUCTED 230V – NO ELECTRIC HEAT STRIP
–R32 – SUBMITTAL (ADP09N3H2)


Job	Reference	Construction
Location	Approval	Quote Number
Engineer	Date	Drawing Number
Submitted To	Submitted By	P.O. Number

General Features

- BLDC inverter compressor
- Onboard touch controller
- ECM fans
- Washable filter
- R32 Refrigerant
- 4 selectable fan speeds + Auto
- Auto restart
- 10-Year limited warranty (after certification)
- Intelligent defrost
- Made in Italy
- No outdoor unit



The installing contractor must contact INNOVA Customer Technical Support prior to installation to schedule an installation training overview. This may be conducted in person or remotely (online). It is the official installation training and may include videos, best practices, and system requirements. Performing installations without training may result in installation errors, performance issues, and possible warranty limitations.



Performance Specifications			
Cooling	Min-Max	BTU/H	15,000 – 3,100
	Rated capacity (95°F)		6,100
	Efficiency	EER2	11.56
Heating	Min-Max	BTU/H	14,000 – 3,500
	Rated capacity (47°F)		8,200
	Rated capacity (5°F)		5,900
	Efficiency	COP	3.73
Sound	Indoor: Low-High at 1 m distance	db(A)	38 – 49
	Indoor: Low-High at 3 m distance		30 – 41
	Outdoor sound range		28 – 55
Moisture removal	Moisture removal	Pts/h	1.8
		L/hr	0.9
Airflow	Indoor	CFM	226 – 400
		m³/hr	384 – 680
	Outdoor	CFM	385 – 638
		m³/hr	654 – 1084

Electric Specifications	
Power Supply	230V/1Ph/60Hz
Voltage Range	180-253
Running Amps Cooling	4.1
Running Amps Heating	5.0
MCA	11
Maximum Overcurrent Protection (A)	15
Max Power Input (amps) Cooling	8.6
Max Power Input (amps) Heating	8.6

Included	Wall Controllers + Gateways	
☐	Wireless Remote	WRCH20
☐	Recessed Touch Controller	RTCH20
☐	Advanced TFT Controller with 7-Day program	TFTH20
☐	Third Party Gateway	TPG015
☐	WiFi Module	WIFI30
☐	E-Paper EOS Controller	EEOS12
☐	Simple EOS Controller	SEOS12
☐	Integration gateway for LTCH20, TFTH20 and MODBUS	GWN
☐	Integration gateway for LTCH20, TFTH20, MODBUS, BACnet, and third-party thermostats	GWX



Bottom return configuration (if required) must be specified at time of order. Standard units are supplied with side returns.

9.9 230V Heat pump + 1,800W elec heat – Energy Star Compliant

AIO™ CEILING DUCTED 230V + 1800W ELECTRIC HEAT – R32 – SUBMITTAL (ADK09N3H2)


Job	Reference	Construction
Location	Approval	Quote Number
Engineer	Date	Drawing Number
Submitted To	Submitted By	P.O. Number

General Features

- BLDC inverter compressor
- ECM fans
- 900/1800W Electric heat supplement
- R32 Refrigerant
- Auto restart
- Intelligent defrost
- No outdoor unit
- Onboard touch controller
- Washable filter
- 4 selectable fan speeds + Auto
- 10-Year limited warranty (after certification)
- Made in Italy



The installing contractor must contact INNOVA Customer Technical Support prior to installation to schedule an installation training overview. This may be conducted in person or remotely (online). It is the official installation training and may include videos, best practices, and system requirements. Performing installations without training may result in installation errors, performance issues, and possible warranty limitations.



Performance Specifications			
Cooling	Min-Max	BTU/H	15,000 – 3,100
	Rated capacity (95°F)		6,100
	Efficiency	EER2	11.56
Heating	Min-Max	BTU/H	14,000 – 3,500
	Rated capacity (47°F)		8,200
	Rated capacity (5°F)		5,900
Sound	Indoor: Low-High at 1 m distance	db(A)	38 – 49
	Indoor: Low-High at 3 m distance		30 – 41
	Outdoor sound range		28 – 55
Moisture removal	Moisture removal	Pts/h	1.8
		L/hr	0.9
Airflow	Indoor	CFM	226 – 400
		m³/hr	384 – 680
	Outdoor	CFM	385 – 638
		m³/hr	654 – 1084

Electric Specifications	
Power Supply	230V/1Ph/60Hz
Voltage Range	180-253
Running Amps Cooling	4.1
Running Amps Heating	5.0
MCA	18
Maximum Overcurrent Protection (A)	20
Max Power Input (amps) Cooling	8.6
Max Power Input (amps) Heating	16.4

Included	Wall Controllers + Gateways	
☐	Wireless Remote	WRCH20
☐	Recessed Touch Controller	RTCH20
☐	Advanced TFT Controller with 7-Day program	TFTH20
☐	Third Party Gateway	TPG015
☐	WiFi Module	WIFI30
☐	E-Paper EOS Controller	EEOS12
☐	Simple EOS Controller	SEOS12
☐	Integration gateway for LTCH20, TFTH20 and MODBUS	GWN
☐	Integration gateway for LTCH20, TFTH20, MODBUS, BACnet, and third-party thermostats	GWX



Bottom return configuration (if required) must be specified at time of order. Standard units are supplied with side returns.

9.10 230V Heat pump + 2,700W elec heat – Energy Star Compliant

AIO™ CEILING DUCTED – 230V – 2,700W ELEC. HEAT – R32
– SUBMITTAL (ADL09N3H2)

Job	Reference	Construction
Location	Approval	Quote Number
Engineer	Date	Drawing Number
Submitted To	Submitted By:	P.O. Number:


General Features

- BLDC inverter compressor
- ECM fans
- Field configured 900W, 1,800W or 2,700W electric heat supplement
- Bathroom exhaust connection
- R32 Refrigerant
- Auto restart
- Intelligent defrost
- No outdoor unit
- Onboard touch controller
- Washable filter
- 4 selectable fan speeds + Auto
- 10-Year limited warranty (after certification)
- Made in Italy



The installing contractor must contact INNOVA Customer Technical Support prior to installation to schedule an installation training overview.

This may be conducted in person or remotely (online) It is the official installation training and may include videos, best practices, and system requirements. Performing installations without training may result in installation errors, performance issues, and possible warranty limitations.



Performance Specifications			
Cooling	Min-Max	BTU/H	3,100 – 15,000
	Rated capacity (95°F)		6,100
	Efficiency	EER2	11.56
Heating	Min-Max	BTU/H	3,500 – 14,000
	Rated capacity (47°F)		8,200
	Rated capacity (5°F)		5,900
	Efficiency	COP	3.73
Sound	Indoor: Low-High at 1 m distance	db(A)	38 – 49
	Indoor: Low-High at 3 m distance		30 – 41
	Outdoor sound range		28 – 55
Moisture removal	Moisture removal	Pts/h	1.8
		L/hr	0.9
Airflow	Indoor	CFM	226 – 400
		m³/hr	384 – 680
	Outdoor	CFM	385 – 638
		m³/hr	654 – 1084

Electric Specifications	
Power Supply	230V/1Ph/60Hz
Voltage Range	180–253
Running Amps Cooling	4.1
Running Amps Heating	5.0
MCA	22
Maximum Overcurrent Protection (A)	25
Max Power Input (amps) Cooling	8.6
Max Power Input (amps) Heating	20.3

Included	Wall Controllers + Gateways	
☐	Wireless Remote	WRCH20
☐	Basic Touch Controller	LTCH20
☐	Recessed Touch Controller	RTCH20
☐	Advanced TFT Controller with 7-Day program	TFTH20
☐	Wireless (AA Battery) Infrared Controller with 7-Day program	WIPT20
☐	Third Party Gateway	TPG015
☐	WiFi Module	WIFI30
☐	E-Paper EOS Controller	EEOS12
☐	Simple EOS Controller	SEOS12
☐	Integration gateway for LTCH20, TFTH20 and MODBUS	GWN
☐	Integration gateway for LTCH20, TFTH20, MODBUS, BACnet, and third-party thermostats	GWX




Bottom return configuration (if required) must be specified at time of order. Standard units are supplied with side returns.



With over 20 years of experience in the climate comfort sector, we have a clear goal: growth through innovation. Our team is laser-focused on the conception, development, and production of innovative heating, ventilation, and air conditioning solutions. This mission has developed through bringing together technical skills, creativity, technology, design, Italian passion, and a global vision to achieve the best energy efficiency and performance.

innova.co | **USA:** 216-710-1000 **Canada:** 416-739-1000



© 2026 INNOVA. All rights reserved.

Revised August 12, 2026

AIO™ Ceiling Ducted Without ERV (Gen 3)

Product Data Sheet